

C6	176	Threshold for high condenser temperature warning	0°F/°C to 199°F/°C Differential = 4°F/2°C
C7	194	Threshold for high condenser temperature alarm	0°F/°C to 199°F/°C
C8	1	High condenser temperature alarm delay	0 min to 15 min
C10	0	Compressor hours for service	0 h to 999 h x 100 0 = Disabled
PAR.	DEF.	DEFROST (if r5 = 0)	MIN. - MAX.
d0	8	Automatic defrost interval	0 h to 99 h 0 = Only manual If d8 = 3, maximum interval
d1	0	Defrost type	0 = Electric 1 = Hot gas 2 = Compressor stopped
d2	46	Threshold for defrost end	-99 to 99 °F/°C
d3	30	Defrost duration	0 min to 99 min If P3 = 1, maximum duration
d4	0	Enable defrost at power-on	0 = no 1 = yes
d5	0	Defrost delay after power-on	0 min to 99 min
d6	2	Value displayed during defrost	0 = Cabinet temperature 1 = Display locked 2 = dEF label
d7	2	Dripping time	0 min to 15 min
d8	0	Defrost interval counting mode	0 = Device on hours 1 = Compressor on hours 2 = Hours evaporator temperature < d9 3 = Adaptive 4 = Real time
d9	32	Evaporation threshold for automatic defrost interval counting	-99°F/°C to 99°F/°C
d11	0	Enable defrost timeout alarm	0 = No 1 = Yes
d15	0	Compressor on consecutive time for hot gas defrost	0 min to 99 min
d16	0	Pre-dripping time for hot gas defrost	0 min to 99 min
d18	40	Adaptive defrost interval	0 min to 999 min If compressor on and evaporator temperature < d22 0 = Only manual
d19	6	Threshold for adaptive defrost, relative to optimal evaporation temperature	0°F/°C to 40°F/°C Optimal evaporation temperature - d19
d20	180	Compressor on consecutive time for defrost	0 min to 999 min 0 = disabled
d21	200	Compressor on consecutive time for defrost after power-on and overcooling	0 min to 500 min If (cabinet temperature - setpoint) > 20°F/10°C 0 = Disabled
d22	-4	Evaporation threshold for adaptive defrost interval counting, relative to optimal evaporation temperature	-10°F/°C to 10°F/°C Optimal evaporation temperature + d22
PAR.	DEF.	ALARMS	MIN. - MAX.
AA	0	Select sensor for high and low temperature alarms	0 = Cabinet temperature 1 = Auxiliary temperature
A1	-20	Threshold for low temperature alarm	-99°F/°C to 99°F/°C
A2	1	Low temperature alarm type	0 = Disabled 1 = Relative to setpoint 2 = Absolute
A4	20	Threshold for high temperature alarm	-99°F/°C to 99°F/°C
A5	1	High temperature alarm type	0 = Disabled 1 = Relative to setpoint 2 = Absolute
A6	12	High temperature alarm delay after power-on	0 min to 99 min x 10
A7	15	High and low temperature alarms delay	0 min to 240 min
A8	15	High temperature alarm delay after defrost	0 min to 240 min
A9	15	High temperature alarm delay after door closing	0 min to 240 min
A10	10	Power failure duration for alarm recording	0 min to 240 min
A11	4	High and low temperature alarms reset differential	1°F/°C to 15°F/°C
A12	2	Power failure alarm notification type	0 = HACCP LED 1 = HACCP LED + PF label + buzzer 2 = HACCP LED + PF label + buzzer (if duration > A10)
A13	0	Enable alarm buzzer	0 = No 1 = Yes
PAR.	DEF.	FANS	MIN. - MAX.
F0	3	Evaporator fan mode during normal operation	0 = Off 1 = On 2 = According to F15 and F16 if compressor off, on if compressor on 3 = Thermoregulated (with F1) 4 = Thermoregulated (with F1) if compressor on
F1	30	Threshold for evaporator fan operation	-99°F/°C to 99°F/°C Differential = 2°F/1°C
F2	0	Evaporator fan mode during defrost and dripping	0 = Off 1 = on 2 = According to F0
F3	2	Evaporator fan off maximum time	0 min to 15 min
F4	0	Evaporator fan off time during energy saving	0 s to 240 s x 10
F5	10	Evaporator fan on time during energy saving	0 s to 240 s x 10
F7	9	Threshold for evaporator fan on after dripping (relative to setpoint)	-99°F/°C to 99°F/°C Setpoint + F7
F9	0	Evaporator fan off delay after compressor off	0 s to 240 s If F0 = 2
F15	0	Evaporator fan off time with compressor off	0 s to 240 s If F0 = 2
F16	1	Evaporator fan on time with compressor off	0 s to 240 s If F0 = 2
PAR.	DEF.	DIGITAL INPUTS	MIN. - MAX.

i0	5	Door switch or multi-purpose input function	0 = Disabled 1 = Compressor + evaporator fan off 2 = Evaporator fan off 3 = n/a 4 = Compressor + evaporator fan off 5 = Evaporator fan off 6 = n/a 7 = Energy saving 8 = iA alarm 9 = Device on or off 10 = Cth alarm 11 = th alarm
i1	0	Door switch or multi-purpose input activation	0 = With contact closed 1 = With contact open
i2	30	Open door alarm delay	-1 min to 120 min -1 = Disabled
i3	15	Regulation inhibition maximum time with door open	-1 min to 120 min -1 = Until the closing
i7	0	Multi-purpose input alarm delay	-1 min to 120 min -1 = Disabled If i0 = 10 or 11, compressor on delay after alarm reset
i10	0	Door closed consecutive time for energy saving	0 min to 999 min After regulation temperature < SP 0 = disabled
i13	180	Number of door openings for defrost	0 to 240 0 = Disabled
i14	32	Door open consecutive time for defrost	0 min to 240 min 0 = Disabled
PAR.	DEF.	ENERGY SAVING (if r5 = 0)	MIN. - MAX.
HE2	0	Energy saving maximum duration	1 min to 999 min 0 = Until the door opening
PAR.	DEF.	REAL TIME ENERGY SAVING (if r5 = 0)	MIN. - MAX.
H01	0	Energy saving time	0 h to 23 h
H02	0	Energy saving duration	0 h to 24 h
HEd	7	Energy saving day	0 = Monday 1 = Tuesday 2 = Wednesday 3 = Thursday 4 = Friday 5 = Saturday 6 = Sunday 7 = None
PAR.	DEF.	REAL TIME DEFROST (if d8 = 4)	MIN. - MAX. (h- = disabled)
Hd1	h-	First daily defrost time	h-, 1 to 24
Hd2	h-	Second daily defrost time	h-, 1 to 24
Hd3	h-	Third daily defrost time	h-, 1 to 24
Hd4	h-	Fourth daily defrost time	h-, 1 to 24
Hd5	h-	Fifth daily defrost time	h-, 1 to 24
Hd6	h-	Sixth daily defrost time	h-, 1 to 24
PAR.	DEF.	SAFETIES	MIN. - MAX.
POF	1	Enable ON/STAND-BY key	0 = No 1 = Yes
PAS	0	Password	-99 to 999 0 = Disabled
PAR.	DEF.	REAL TIME CLOCK	MIN. - MAX.
HR0	0	Enable clock	0 = No 1 = Yes
PAR.	DEF.	MODBUS	MIN. - MAX.
LA	247	MODBUS address	1 to 247
Lb	2	MODBUS baud rate	0 = 2,400 baud 1 = 4,800 baud 2 = 9,600 baud 3 = 19,200 baud Parity even

8 ALARMS

COD.	DESCRIPTION	RESET	REMEDIES
Pr1	Cabinet probe alarm	Automatic	- Check P0
Pr2	Auxiliary probe alarm	Automatic	- Check probe integrity - Check electrical connection
rtc	Clock alarm	Manual	Set date, time, and day of the week
AL	Low temperature alarm	Automatic	Check AA, A1, and A2
AH	High temperature alarm	Automatic	Check AA, A4, and A5
id	Open door alarm	Automatic	Check i0 and i1
PF	Power failure alarm	Manual	- Tap any key - Check electrical connection
COH	High condenser temperature warning	Automatic	Check C6
CSd	High condenser temperature alarm	Manual	- Switch the device off and on - Check C7
IA	Multi-purpose input alarm	Automatic	Check i0 and i1
Cth	Compressor thermal switch alarm	Automatic	Check i0 and i1
th	Global thermal switch alarm	Manual	- Switch the device off and on - Check i0 and i1
dFd	Defrost timeout alarm	Manual	- Tap any key - Check d2, d3 and d11

9 ELECTRICAL RATINGS

Output	Units	cULus (UL 60730)		CE (EN 60730)
	Applied voltage at 60 Hz	120 VAC	240 VAC	240 VAC
K1 compressor relay	Resistive amperes	12	12	12
	Inductive amperes	—	—	2
	Full load amperes	10	10	—
	Locked rotor amperes	60	60	—
K2 relay	Resistive amperes	8	8	5
	Inductive amperes	—	—	2
	Full load amperes	4.4	2.9	—
	Locked rotor amperes	26.4	17.4	—
K3 evaporator fan relay	Resistive amperes	5	5	5
	Inductive amperes	—	—	1
	Full load amperes	1.5	1.5	—
	Locked rotor amperes	9	9	—

10 TECHNICAL SPECIFICATIONS

Purpose of the control device	Function controller
Construction of the control device	Built-in electronic device
Container	Black, self-extinguishing
Category of heat and fire resistance	D
Measurements	2 15/16 in. x 1 5/16 in. x 2 5/16 in. (75 mm x 33 mm x 59 mm)
Mounting methods for the control device	Fit the controller to a panel with the snap-in brackets supplied
Degree of protection provided by the covering	IP65 in front
Connection method	
Fixed screw terminal blocks for wires up to 2.5 mm ²	Micro-MaTch® connector

Maximum permitted length for connection cables		
Power supply: 32.8 ft (10 m)	Analog inputs: 32.8 ft (10 m)	
Digital inputs: 32.8 ft (10 m)	Digital outputs: 32.8 ft (10 m)	
Operating temperature	From 32°F to 131°F (from 0°C to 55°C)	
Storage temperature	From -13°F to 158°F (from -25°C to 70°C)	
Operating humidity	Relative humidity without condensate from 10% to 90%	
Pollution status of the control device	2	
Compliance		
United States	cURus Recognized: File SA32187 CCN SDFY2: FCC Compliant to CFR47, Part 15, Subpart B, Class A limits	
Canada	cURus Recognized: File SA32187 CCN SDFY8: Industry Canada (IC) compliant to Canadian ICES-003, Class A limits	
Europe	CE Mark – Johnson Controls declares that this product is in compliance with the essential requirements and other relevant provisions of the EMC Directive, Low Voltage Directive, and RoHS Directive	
Power supply	TC3223N5x 115 VAC (+10% -15%), 50/60 Hz (+/- 3Hz), max. 2 VA TC3223N7x 230 VAC (+10% -15%), 50/60 Hz (+/- 3Hz), max. 2 VA	
Grounding methods for the control device	None	
Rated impulse-withstand voltage	4 KV	
Over-voltage category	III	
Software class and structure	A	
Analog inputs	2 for NTC probes (cabinet probe and auxiliary probe)	
NTC probes	Sensor type	B3435 (10 KΩ at 77°F, 25°C)
	Measurement field	-40°F to 221°F (-40°C to 105°C)
	Resolution	1°F (0.1°C)
Digital inputs	1 dry contact (door switch/multi-purpose)	
Dry contact	Contact type	5 VDC, 1.5 mA
	Power supply	None
	Protection	None
Digital outputs	3 electro-mechanical relays (compressor, defrost and evaporator fan)	
Type 1 or Type 2 actions	Type 1	
Additional features of Type 1 or Type 2 actions	C	
Displays	3 digits custom display with function icons	
Alarm buzzer	Incorporated	
Communication ports	1 TTL MODBUS subordinate port for BMS	

11 PRODUCT WARRANTY

This product is covered by a limited warranty, details of which can be found at www.johnsoncontrols.com/buildingswarranty

12 SOFTWARE TERMS


Use of the software that is in (or constitutes) this product, or access to the cloud, or hosted services applicable to this product, if any, is subject to applicable end-user license, open-source software information, and other terms set forth at www.johnsoncontrols.com/techterms. Your use of this product constitutes an agreement to such terms.

13 SINGLE POINT OF CONTACT

APAC	Europe	NA/SA
JOHNSON CONTROLS C/O CONTROLS PRODUCT MANAGEMENT NO. 32 CHANGJIANG RD NEW DISTRICT WUXI JIANGSU PROVINCE 214028 CHINA	JOHNSON CONTROLS WESTENDHOF 3 45143 ESSEN GERMANY	JOHNSON CONTROLS 507 E MICHIGAN ST MILWAUKEE WI 53202 USA

14 CONTACT INFORMATION

Contact your local branch office:
www.johnsoncontrols.com/locations
Contact Johnson Controls:
www.johnsoncontrols.com/contact-us



This document and the solutions contained therein are the intellectual property of Penn and thus protected by the Italian Intellectual Property Rights Code (CPI). Penn imposes an absolute ban on the full or partial reproduction and disclosure of the content other than with the express approval of Penn. The customer (manufacturer, installer or end-user) assumes all responsibility for the configuration of the device. Penn accepts no liability for any possible errors in this document and reserves the right to make any changes, at any time without prejudice to the essential functional and safety features of the equipment.



Johnson Controls
507 E. Michigan St.
Milwaukee, WI 53202-5211
USA
www.penncontrols.com